


歐式端子

Non-Insulated Cord-End Sleeves

(DIN-46228/1) (Material : Copper tube, Tin plated)



Unit:mm

Unit:mm

ITEM NO.	WIRE RANGE mm ² AWG	L	φ d1 unit : mm	φ D1	φ D2
CN 0.5-6		6			
CN 0.5-8	0.50	8	1.0	1.3	2.1
CN 0.5-10	22	10			
CN 0.75-6		6			
CN 0.75-8	0.75	8	1.2	1.5	2.3
CN 0.75-10	20	10			
CN 1.0-6		6			
CN 1.0-8	1.00	8	1.4	1.7	2.5
CN 1.0-10	18	10			
CN 1.0-12		12			
CN 1.5-7		7			
CN 1.5-8	1.50	8	1.7	2.0	2.8
CN 1.5-10	16	10			
CN 1.5-12		12			
CN 2.5-7		7			
CN 2.5-8		8			
CN 2.5-10	2.50	10	2.2	2.5	3.4
CN 2.5-12	14	12			
CN 2.5-18		18			
CN 4-8		8			
CN 4-9		9			
CN 4-10	4.00	10	2.8	3.2	4.0
CN 4-12	12	12			
CN 4-15		15			
CN 4-18		18			
CN 6-10		10			
CN 6-12	6.00	12	3.5	3.9	4.7
CN 6-15	10	15			
CN 6-18		18			
CN 10-12		12			
CN 10-15	10.00	15	4.5	4.9	5.8
CN 10-18	8	18			

ITEM NO.	WIRE RANGE mm ² AWG	L	φ d1 unit : mm	φ D1	φ D2
CN 16-12		12			
CN 16-15	16.00	15	5.8	6.2	7.5
CN 16-18	6	18			
CN 25-15		15			
CN 25-16		16			
CN 25-18	25.00	18	7.3	7.7	9.5
CN 25-20	4	20			
CN 25-22		22			
CN 35-16		16			
CN 35-18	35.00	18	8.3	8.7	11.0
CN 35-20	2	20			
CN 35-25		25			
CN 50-18		18			
CN 50-20	50.00	20	10.3	10.9	13.0
CN 50-22	1/0	22			
CN 50-25		25			
CN 70-22		22			
CN 70-25	70.00	25	13.5	14.3	15.3
CN 70-32	2/0	32			
CN 95-25	95.00	25			
CN 95-32	3/0	32	14.7	15.5	16.6
CN 120-30		30			
CN 120-32	120.00	32	16.7	17.6	18.6
CN 120-34	4/0	34			
CN 150-32	150.00	32	19.5	20.5	21.5
CN 150-38	250-300	38			
MCM					

★ Specifications for reference only; changing w/o prior notice.