


R型銅管高導電端子

Cable Lugs (General size) (CL type)

(w / lookout window) (有檢驗孔)



ITEM NO.	φd2	φd1	φD	B	E	F	L	DINmm ²
CL 2.5-4	4.3			8.0			18	
CL 2.5-5	5.3	2.4	3.9	8.0	7	7	18	2.5
CL 2.5-6	6.4			10.0			19	
CL 4-5	5.3	2.8	4.5	10.0	7	8	20	4
CL 4-6	6.4							
CL 6-5	5.3			10.0			23	
CL 6-6	6.4	3.8	5.5	10.0	9	9	23	6
CL 6-8	8.4			12.6			25	
CL 10-5	5.3			10.0			25	
CL 10-6	6.4	4.5	6.2	10.0	9	10	25	10
CL 10-8	8.4			12.6			26	
CL 16-5	5.3			10.0				
CL 16-6	6.4			10.0				
CL 16-8	8.4	5.4	7.1	12.6	12	11	30	16
CL 16-10	10.5			12.6				
CL 25-6	6.4			12.6		11	30	
CL 25-8	8.4	6.8	8.8	12.6	12	11	30	25
CL 25-10	10.5			15.0		12.5	32	
CL 35-6	6.4			15.0		13	35	
CL 35-8	8.4	8.2	10.6	15.0	13	14	35	35
CL 35-10	10.5			15.0		13	35	
CL 35-12	13.0			18.6		12	36.8	
CL 50-8	8.4			18.0				
CL 50-10	10.5	9.5	12.4	18.0	16	17	43	50
CL 50-12	13.0			19.0				
CL 70-8	8.4							
CL 70-10	10.5	11.2	14.7	21.0	18	20	50	70
CL 70-12	13.0							
CL 95-8	8.4							
CL 95-10	10.5	13.5	17.4	25.5	20	22	55	95
CL 95-12	13.0							
CL 120-10	10.5							
CL 120-12	13.0	15.0	19.4	28.0	22	24	60	120
CL 120-14	15.0							
CL 120-16	17.0							

ITEM NO.	φd2	φd1	φD	B	E	F	L	DINmm ²
CL 150-8	8.4							
CL 150-10	10.5							
CL 150-12	13.0	16.5	21.2	30.5	26	27	69	150
CL 150-14	15.0							
CL 150-16	17.0							
CL 185-8	8.4							
CL 185-10	10.5							
CL 185-12	13.0	18.5	23.5	34.0	32	29	78	185
CL 185-14	15.0							
CL 185-16	17.0							
CL 240-12	13.0							
CL 240-14	15.0	21.0	26.5	38.5	38	34	92	240
CL 240-16	17.0							
CL 240-18	19.0							
CL 300-12	13.0							
CL 300-14	15.0	23.5	30.0	43.5	42	37	101	300
CL 300-16	17.0							
CL 300-18	19.0							
CL 400-12	13.0							
CL 400-16	17.0	28.5	36.5	53.0	44	44	114	400
CL 400-18	19.0							
CL 400-20	21.0							
CL 500-16	17.0							
CL 500-18	19.0	30.0	39.0	56.0	48	48	124	500
CL 500-20	21.0							
CL 625-16	17.0							
CL 625-18	19.0	34.5	44.0	63.5	52	51	130	625
CL 625-20	21.0							
CL 800-16	17.0							
CL 800-18	19.0	40.0	51.2	74.0	54	56	140	800
CL 800-20	21.0							
CL 1000-16	17.0							
CL 1000-18	19.0	44.0	56.6	81.5	60	56	146	1000
CL 1000-20	21.0							